

VARIABLE SPEED, WITH DIGITAL DISPLAY OF SPINDLE SPEED AND DIGITAL DISPLAY OF DEPTH.



<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 28 mm
<b>Face milling cutter max</b>	Ø 63 mm
<b>End milling capacity</b>	Ø 28 mm
<b>Spindle taper</b>	CM 3
<b>Chuck sizes</b>	3 - 16 mm B16
<b>Spindle speed</b>	100 - 2500 rpm ±10%
<b>Spindle rotation</b>	L - R
<b>Spindle stroke</b>	70 mm
<b>Quill</b>	70 mm
<b>Headstock travel</b>	380 mm
<b>Head tilt left and right</b>	±90°
<b>Table dimensions</b>	730 x 210 mm
<b>Slot</b>	14 mm
<b>Longitudinal axis</b>	190 mm
<b>Cross axis</b>	440 mm
<b>Motor</b>	230 V 50 Hz 1,1 kW
<b>Net weight</b>	270 kg
<b>Packaging dimensions</b>	930x720x1116 h mm
<b>Gross weight</b>	290,00 kg
<b>EAN Code</b>	8012667312701

### Included

Drill chuck with key 3 - 16 mm B16  
Spindle drilled MT 3  
Oilcan  
Draw bar M12  
Service wrenches