

REVERSIBLE, WITH AUTOMATIC FEEDING, COOLANT SYSTEM AND EQUIPPED WITH LIGHT, PARTIALLY ROTATING TABLE.



FERVIplus



Max drilling capacity on cast iron with pre-drilling hole	Ø 45 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 40 mm
Continuous drilling capacity	Ø 35 mm
Spindle taper	MT 4
Chuck sizes	1 - 13 mm B16
Spindle speed	(18) 50 - 1450 rpm
Spindle travel	180 mm
Spindle rotation	Dx - Sx
Quill	Ø 75 mm
Column	Ø 150 mm
Feed range	(2) 0,1 - 0,20 mm/rev
Distance between spindle axis and column	350 mm
Distance between spindle nose and table	780 mm
Distance between spindle nose and base	1320 mm
Table dimensions	560 x 560 mm
Slot	18 mm
Tilting table	±90°
Base dimensions	500 x 730 mm
Motor	400 V 50 Hz 1,5 / 2,4 kW
Cooling pump	400 V 50 Hz 40 W
Dimensions	935 x 530 x 2280 mm
Net weight	550 kg
Packaging dimensions	2275 x 1100 x 575 h mm

Included

Key type drill chuck 1- 13 mm B16
Drill chuck arbor MT4 B16
Reduction sleeve MT 4/3
Reduction sleeve MT 3/2

Gross weight

600,00 kg

EAN Code

8012667340582