

HYDRAULIC LOCKING BETWEEN ARM AND COLUMN, REVERSIBLE,
 WITH AUTOMATIC FEEDING, COOLANT SYSTEM, EQUIPPED WITH LED
 LIGHT. WITH GEAR..



Max drilling capacity on cast iron with pre-drilling hole	Ø 50 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 40 mm
Continuous drilling capacity	Ø 40 mm
Spindle taper	MT 4
Chuck sizes	-
Spindle speed	(12) 40 - 1896 rpm
Spindle travel	260 mm
Quill	Ø 67 mm
Column	280 mm
Distance spindle axis - column surface	1370 mm
Distance between spindle nose and table	840 mm
Distance between spindle nose and base	1210 mm
Feed range	(4) 0.13 - 0.54 mm/rev
Cube dimensions	610 x 460 x 370 mm
Slot	16 mm 20 mm
Base dimensions	1960 x 800 mm
Motor	400 V 50 Hz 3,0 kW
Lifting motor radial arm	400 V 50 Hz 0,75 kW
Cooling pump	400 V 50 Hz 90 W
Dimensions	2050 x 820 x 2480 mm
Net weight	2100 kg
Packaging dimensions	2160x1050x2310 h mm
Gross weight	2250,00 kg

