

VERTICAL MOVEMENT OF THE TABLE WITH RACK, TILTING TABLE.
ELECTRICAL SYSTEM WITH SEPARATE 24V CIRCUIT FOR ON-BOARD
MACHINE...



| | |
|--|----------------------|
| Max drilling capacity on cast iron with pre-drilling hole | Ø 13 mm |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 10 mm |
| Chuck sizes | 1 - 13 mm B16 |
| Self-centering chuck | 13 mm |
| Spindle speed | (5) 620 - 2620 rpm |
| Spindle travel | 65 mm |
| Quill | Ø 40 mm |
| Column | Ø 58 mm |
| Height | 690 mm |
| Distance spindle axis - column surface | 130 mm |
| Distance between spindle nose and base | 330 mm |
| Table dimensions | 190 x 200 mm |
| Tilting table | ± 45° |
| Motor | 230 V 50 Hz 0,375 kW |
| Dimensions | 315 x 530 x 690h mm |
| Net weight | 25 kg |
| Gross weight | 27,00 kg |
| EAN Code | 8012667371791 |
| Packaging dimensions | 580x420x260 h mm |

Included

Keyless chuck 1 - 13 mm B16