



WITH MECHANICAL SPINDLE CLUTCH AND 3 AXIS READ OUT, SEMI NORTON GEAR BOX. EQUIPPED WITH A JOYSTICK FOR THE INSERTION OF RAPID...



Centers height	250 mm
Max swing over the bed	500 mm
Max swing over the cross slide	310 mm
Max swing over the gap	720 mm
Tool height	32 mm
Distance between centers	2000 mm
Spindle bore	80 mm
Spindle nose Camlock	Camlock D1-8
Spindle bore taper MT	7
Spindle speed	(12) 36 - 1600 rpm
Longitudinal feeds	0,063 - 2,52 mm/giro
Cross feeds	0,027 - 1,07 mm/rev
Metric threads	(22) 1 - 14 mm
Inch threads	(26) 2 - 28 TPI
Tailstock taper MT	5
Motor	400V 50/60 Hz 7,5 kW
Cooling pump	400V 50/60 Hz 90 W
Dimensions	3500 x 1400 x 1500 mm
Net weight	3320 kg
EAN Code	8012667376345

Included

- 3 reversible jaw self centering chuck Ø 250 mm
- 4 independent jaw chuck Ø 320 mm
- Reduction sleeve MT 7/5
- Face plate Ø 400 mm
- Follow rest
- Steady rest
- 2 x Dead center MT 5
- Live center MT 5
- Thread dial
- Leadscrew hood
- Turret guard
- Chuck safeguard
- Full length splash guard
- Italy style quick change tool post type C
- Working LED lamp
- Cooling system
- Electromechanical foot brake
- Tailstock carriage a quick locking
- Wagon gears in oil bath
- Adjustable leveling feet