



WITH MECHANICAL SPINDLE CLUTCH AND 3 AXIS READ OUT, SEMI NORTON GEAR BOX. EQUIPPED WITH A JOYSTICK FOR THE INSERTION OF RAPID...



<b>Centers height</b>	280 mm
<b>Max swing over the bed</b>	560 mm
<b>Max swing over the cross slide</b>	360 mm
<b>Max swing over the gap</b>	770 mm
<b>Tool height</b>	32 mm
<b>Distance between centers</b>	1000 mm
<b>Spindle bore</b>	105 mm
<b>Spindle nose Camlock</b>	Camlock D1-8
<b>Spindle speed</b>	(12) 36 - 1600 rpm
<b>Longitudinal feeds</b>	0,063 - 2,52 mm/giro
<b>Cross feeds</b>	0,027 - 1,07 mm/giro
<b>Metric threads</b>	(22) 1 - 14 mm
<b>Inch threads</b>	(26) 2 - 28 TPI
<b>Tailstock taper MT</b>	5
<b>Motor</b>	400V 50/60 Hz 7,5 kW
<b>Cooling pump</b>	400V 50/60 Hz 90 W
<b>Dimensions</b>	2500 x 1400 x 1500 mm
<b>Net weight</b>	2920 Kg
<b>Gross weight</b>	3555,00 kg
<b>EAN Code</b>	8012667402013

### Included

3 reversible jaw self centering chuck Ø 320 mm  
 4 independent jaw chuck Ø 400 mm  
 Face plate Ø 600 mm  
 Follow rest  
 Steady rest  
 Live center MT 5  
 Thread dial  
 Leadscrew hood  
 Tool post guard  
 Chuck safeguard  
 Full length splash guard  
 Italy style quick change tool post type C  
 Working LED lamp  
 Cooling system  
 Electromechanical foot brake  
 Tailstock carriage a quick locking  
 Wagon gears in oil bath  
 Adjustable leveling feet