

WITH SEMI NORTON GEAR BOX. TURNING BAR WITH ADJUSTABLE CLUTCH.



Centers height	160 mm
Max swing over the bed	320 mm
Max swing over the cross slide	180 mm
Tool height	16 mm
Distance between centers	1000 mm
Spindle bore taper MT	5
Spindle bore	38 mm
Spindle nose Camlock	Camlock D1-4
Spindle speed	(18) 75-1800 rpm
Longitudinal feeds	(40) 0,053 - 1,291 mm/rev
Cross feeds	(40) 0,011 - 0,275 mm/rev
Metric threads	(32) 0,4 - 7 mm
Inch threads	(36) 4 - 60 TPI
Tailstock taper MT	3
Motor	400 V 50/60 Hz 1.3 kW
Dimensions	1850 x 700 x 1550 mm
Net weight	550 Kg
Gross weight	540,00 kg
EAN Code	8012667406325

Included

- 3+3 jaw self centering chuck Ø 160 mm
- 4 Reversible independent jaws chuck Ø 200 mm
- Face plate Ø 250 mm
- Follow rest
- Steady rest
- Reduction sleeve MT 5/3
- Dead center MT 3
- Dead center MT 5
- Live center MT 3
- Foot brake
- Thread dial
- Leadscrew protection
- Turret protection
- Chuck safeguard
- Full length splash guard
- TOAE quick change tool post
- Working lamp LED
- Quick locking tailstock carriage
- Cooling system
- Clutch on turning bar
- Wagon gears in oil bath