

PARTIALLY ROTATING TABLE, WITH 125MM VICE.



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 31,75 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 31,75 mm
<b>Spindle taper</b>	MT 3
<b>Continuous drilling capacity</b>	Ø 25 mm
<b>Chuck sizes</b>	1 - 16 B18
<b>Spindle speed</b>	(9) 160 - 1880 rpm
<b>Spindle travel</b>	130 mm
<b>Column</b>	Ø 102 mm
<b>Distance between spindle axis and column</b>	230 mm
<b>Distance between spindle nose and table</b>	700 mm
<b>Distance between spindle nose and base</b>	1175 mm
<b>Table dimensions</b>	330 x 380 mm
<b>Travel of table</b>	670 mm
<b>Slot</b>	14 mm
<b>Base dimensions</b>	300 x 325 mm
<b>Motor</b>	400V 50Hz 1,5 kW
<b>Overall sizes</b>	900 x 430 x 1760 mm
<b>Net weight</b>	280 kg
<b>Packaging dimensions</b>	930x460x1940 h mm
<b>Gross weight</b>	280,00 kg
<b>EAN Code</b>	8012667226848

**Included**

Drill chuck with key 1 - 16 B18  
Spindle drilled MT 3  
Reduction sleeve MT 3/2