

NEW BELT TENSION DEVICE, DRILLING DEPTH READOUT, LED LIGHT INCLUDED, ROTATING AND INCLINABLE TABLE. ELECTRICAL SYSTEM WITH...



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	∅ 20 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	∅ 16 mm
<b>Continuous drilling capacity</b>	∅ 12 mm
<b>Spindle taper</b>	CM 2
<b>Chuck sizes</b>	1 - 13 mm B16
<b>Spindle speed</b>	(16) 180 - 2770 rpm
<b>Spindle travel</b>	85 mm
<b>Quill</b>	∅ 40 mm
<b>Column</b>	∅ 72 mm
<b>Height</b>	980 mm
<b>Distance chuck-column</b>	160 mm
<b>Distance between spindle nose and table</b>	435 mm
<b>Distance between spindle nose and base</b>	625 mm
<b>Table dimensions</b>	305 x 305mm
<b>Slot</b>	16 mm
<b>Tilting table</b>	± 45°
<b>Motor</b>	230 V 50 Hz 0,55 kW
<b>Net weight</b>	50 kg
<b>Gross weight</b>	52,00 kg
<b>EAN Code</b>	8012667254209
<b>Packaging dimensions</b>	890x570x340 h mm

**Included**

Keyless chuck 1 - 13 B16  
Drill chuck shank MT 2