

ROTATING AND INCLINABLE TABLE. ELECTRICAL SYSTEM WITH SEPARATE 24V CIRCUIT FOR ON-BOARD MACHINE CONTROLS.



Max drilling capacity on cast iron with pre-drilling hole	Ø 25 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 20 mm
Continuous drilling capacity	Ø 16 mm
Spindle taper	CM 2
Chuck sizes	1 - 16 mm B18
Spindle speed	(16) 220 - 2840 rpm
Spindle travel	80 mm
Quill	Ø 47 mm
Column	Ø 80 mm
Height	990 mm
Distance spindle axis - column surface	175 mm
Distance between spindle nose and table	420 mm
Distance between spindle nose and base	600 mm
Table dimensions	290 x 290 mm
Slot	14 mm
Tilting table	± 45°
Turning table	Yes
Base dimensions	460 x 275 mm
Motor	230 V 50 Hz 0,75 kW
Dimensions	300 X 630 X 990h mm
Net weight	57 kg
Packaging dimensions	900x570x335 h mm
Gross weight	61,50 kg

Included

Keyless chuck 1 - 16 B18
Drill chuck shank MT 2
Cones remover
Allen keys

