

CON SONDA PER MISURAZIONE TEMPERATURA, CONTINUITÀ SONORA  
E CONTROLLO DIODI.



**€79,50**  
**€98,20**



|                            |   |
|----------------------------|---|
| <b>DCV</b>                 | 200 mV - 2 V - 20 V - 200 V - 1000 V<br>±0,8%             |
| <b>ACV</b>                 | 200 mV - 2 V - 20 V - 750 V ±1,2%                         |
| <b>DCA / ACA</b>           | 200 µA - 2 mA - 20 mA - 200 mA - 20 A<br>±2.0%            |
| <b>RES</b>                 | 200Ω - 2kΩ - 20kΩ - 200kΩ - 2MΩ -<br>20MΩ - 200MΩ ±1%     |
| <b>CAP</b>                 | 20 nF / 200 nF / 2 µF / 20 µF / 200 µF /<br>2000 µF ±2,5% |
| <b>Induttanza</b>          | 2 mH - 20mH - 200 mH - 2 H - 20 H                         |
| <b>Batteria</b>            | 1 x 9 V   |
| <b>Temperatura</b>         | -20 °C - 1000 °C  |
| <b>Frequenza</b>           | 10 mHz  |
| <b>Test transistor hFE</b> | 0 ~ 1000  |
| <b>Peso lordo</b>          | 0,63 kg   |
| <b>Codice EAN</b>          | 8012667183066   |



Scatola

**Accessori  
Inclusi**

Coppia di puntali  
Batteria 9V  
2 sonde per il controllo  
della temperatura  
Fusibile di ricambio